

**COMEUP
WINCH**

Getting you through since 1975



*Built to be Unstoppable.
Trusted by off-roaders worldwide.*

COMEUP INDUSTRIES INC.

No.139, Jieyukeng Rd., Ruifang Dist.,
New Taipei City 224013, Taiwan
<https://www.facebook.com/COMEUP>

Tel : +886-2-24971788 / Fax : +886-2-24971699
E-mail : info@comeup.com.tw
<https://www.comeupwinch.com>

Copyright © COMEUP INDUSTRIES INC. All rights reserved. COMEUP is registered trademark of COMEUP INDUSTRIES INC.
Products may look different than show here. Specifications are subject to change without prior notice.
COMEUP reserves the right to improve our products at any time.




TRAIL EDITION

for SOLO / Seal / Slim Winch



- Waterproof IP68
- Built-in Wireless Controller
- I4WDTA PTRP
- Trail Edition Featuring BossHook and Winch Fuse



**COMEUP
WINCH**

Getting you through since 1975

Explore the Trail Edition. Built to be Unstoppable.

The Trail Edition is the ultimate winch designed for overland expeditions, covering the SOLO, Seal, and Slim Series from 9,500 to 20,000 lbs. Equipped with the innovative BossHook and a specialized Winch Fuse Kit, it delivers superior functionality and protection. Built for reliability and durability, the Trail Edition empowers you to conquer mud, snow, and rocky terrain with unstoppable confidence.

SOLO Series - Trusted by the Experts

◆ 9,500 lb pulling capacity



SOLO 9.5rs Trail Edition
PN 291663 12V, 10 mm x 23.2 m (3/8" x 76') Synthetic Rope, BossHook M, 250A fuse kit

◆ 12,500 lb pulling capacity



SOLO 12.5rs Trail Edition
PN 291500 12V, 11 mm x 21 m (7/16" x 69') Synthetic Rope, BossHook M, 250A fuse kit

Seal Series - Proven Durability

◆ 16,500 lb pulling capacity



Seal 16.5rs Trail Edition
PN 298115 12V, 12.7 mm x 25 m (1/2" x 82') Synthetic Rope, BossHook L, 200A fuse kit



Seal 16.5rsi Trail Edition
PN 298341 12V, 12.7 mm x 25 m (1/2" x 82') Synthetic Rope, BossHook L, 200A fuse kit

◆ 20,000 lb pulling capacity



Seal 20.0rs Trail Edition
PN 298210 12V, 14 mm x 16.7 m (9/16" x 55') Synthetic Rope, BossHook L, 250A fuse kit

Line Speed and Amp. Draw (1st layer of rope on the drum):

SOLO 9.5rs TE / Slim 9.5rs TE / Slim 9.5rsi TE		
Line Pull, kg / lb	Line Speed, mpm / fpm	Amp. Draw, A 12V
No load	14.8 / 48.6	60
907 / 2,000	4.8 / 15.7	115
1,814 / 4,000	3.6 / 11.8	210
2,722 / 6,000	2.8 / 9.2	245
3,629 / 8,000	2.3 / 7.6	280
4,309 / 9,500	2.2 / 7.2	380

SOLO 12.5rs TE / Slim 12.5rs TE / Slim 12.5rsi TE		
Line Pull, kg / lb	Line Speed, mpm / fpm	Amp. Draw, A 12V
No load	7.7 / 25.3	60
907 / 2,000	3.4 / 11.2	115
1,814 / 4,000	2.5 / 8.2	160
2,722 / 6,000	2.0 / 6.6	220
3,629 / 8,000	1.7 / 5.6	275
5,670 / 12,500	0.9 / 3.0	380

Seal 16.5rs TE / Seal 16.5rsi TE		
Line Pull, kg / lb	Line Speed, mpm / fpm	Amp. Draw, A 12V
No load	5.6 / 18.4	50
1,814 / 4,000	3.0 / 9.8	90
3,629 / 8,000	2.5 / 8.2	180
4,536 / 10,000	1.9 / 6.2	230
7,484 / 16,500	1.4 / 4.6	355

Seal 20.0rs TE		
Line Pull, kg / lb	Line Speed, mpm / fpm	Amp. Draw, A 12V
No load	4.5 / 14.8	60
1,814 / 4,000	2.1 / 6.9	150
3,629 / 8,000	1.8 / 5.9	190
4,536 / 10,000	1.4 / 4.6	260
7,484 / 16,500	1.1 / 3.6	340
9,072 / 20,000	0.4 / 1.3	410

Slim Series - Compact Strength Low profile integrated winch

◆ 9,500 lb pulling capacity



Slim 9.5rs Trail Edition
PN 295135 12V, 10 mm x 23.2 m (3/8" x 76') Synthetic Rope, BossHook M, 250A fuse kit



Slim 9.5rsi Trail Edition
PN 295022 12V, 10 mm x 23.2 m (3/8" x 76') Synthetic Rope, BossHook M, 250A fuse kit

◆ 12,500 lb pulling capacity



Slim 12.5rs Trail Edition
PN 295114 12V, 11 mm x 21 m (7/16" x 69') Synthetic Rope, BossHook M, 250A fuse kit



Slim 12.5rsi Trail Edition
PN 295073 12V, 11 mm x 21 m (7/16" x 69') Synthetic Rope, BossHook M, 250A fuse kit

- ◆ On/off switch turns receiver off for extended storage periods.
- ◆ The winch control unit is integrated with the motor.
- ◆ Low profile integrated winch models
Slim 9.5rsi 9,500 lb winch
Slim 12.5rsi 12,500 lb winch
Seal 16.5rsi 16,500 lb winch
- ◆ Clutch handle can be rotated to 16 different positions to allow easy access in any installation configuration.
- ◆ BossHook
Forged from premium SCM440 steel alloy, the BossHook redefines toughness, ensuring superior strength and safety in every recovery. Its silicone rubber pad prevents fairlead damage, while the streamlined design provides a sleek, flush-mounted finish. Easy to install, it's ready when adventure calls.
PN 884344 BossHook L : 1.8" thick when folded flat, with a Minimum Breaking Strength (MBS) of 18,200 kg.
PN 884343 BossHook M : 1.5" thick when folded flat, with a Minimum Breaking Strength (MBS) of 14,500 kg.
- ◆ Winch Fuse Kit
The Winch Fuse Kit protects your winch motor and control system from amperage overloads and short circuits. With this intelligent safeguard, you'll enjoy stable performance and lasting reliability on every recovery.
PN 884104 250A fuse kit - for 9,500 / 12,500 / 20,000 lb winch
PN 884102 200A fuse kit - for 16,500 lb winch
- ◆ Motor can be rotated to three different positions for a wide range of installation options.
- ◆ Built-in wireless remote control module

Line Pull and Rope Capacity:

SOLO 9.5rs TE / Slim 9.5rs TE / Slim 9.5rsi TE			SOLO 12.5rs TE / Slim 12.5rs TE / Slim 12.5rsi TE			Seal 16.5rs TE / Seal 16.5rsi TE			Seal 20.0rs TE		
Layer of Rope	Pull by layer, kg / lb	Total Rope on the Drum, m / ft	Layer of Rope	Pull by layer, kg / lb	Total Rope on the Drum, m / ft	Layer of Rope	Pull by layer, kg / lb	Total Rope on the Drum, m / ft	Layer of Rope	Pull by layer, kg / lb	Total Rope on the Drum, m / ft
1 st	4,309 / 9,500	5.1 / 16.7	1 st	5,670 / 12,500	4.8 / 15.7	1 st	7,484 / 16,500	5.2 / 17.1	1 st	9,072 / 20,000	4.6 / 14.9
2 nd	3,472 / 7,655	11.7 / 38.4	2 nd	4,499 / 9,919	10.9 / 35.7	2 nd	6,125 / 13,503	11.6 / 38.1	2 nd	7,133 / 15,725	10.3 / 33.9
3 rd	2,908 / 6,410	19.7 / 64.6	3 rd	3,729 / 8,221	18.5 / 60.7	3 rd	5,184 / 11,429	19.2 / 63.0	3 rd	5,877 / 12,956	16.7 / 55.0
4 th	2,501 / 5,514	23.2 / 76.0	4 th	3,184 / 7,020	21.0 / 69.0	4 th	4,494 / 9,908	25.0 / 82.0			